



NXB-63H Miniature circuit breaker

1. Compliant standards

IEC/EN60898-1

2. Compliant certification

CE, SII, SI

3. Major function

Overload protection, short circuit protection , positive isolation

4. Technical parameters

Rated current: 1A, 2A, 3A, 4A, 6A, 10A, 16A, 20A, 25A, 32A, 40A, 50A, 63A,;

Rated voltage: 220V~/230V~/240V~(1P, 1P+N) 380V~/400V~/415V~(2~4P, 3P+N);

Frequency: 50/60Hz;

Electromagnetic release type: B, C, D;

Number of poles: 1P, 1P+N, 2P, 3P, 3P+N, 4P;

Mechanical life: 20000 cycles;

Electrical life: 10000 cycles;

Rated short-circuit breaking capacity: 10000A;

Short-circuit breaking capacity: 7500A;

Rated impulse withstand voltage: 4kV;

Power consumption on each pole of the circuit breaker: see Table 1.

Table 1

| Rated current I_n (A) | Maximum power consumption per pole (W) |
|-------------------------|--|
| 1~10 | 3 |
| 16 | 3.5 |
| 20~25 | 4.5 |
| 32 | 6 |
| 40 | 7.5 |
| 50 | 9 |
| 63 | 13 |

5. Dimensions and installation sizes

